

Intellectual Property Network

Home | Search | Order | Shopping Cart | Login | Site Map | Help





View Images (1 pages) | View INPADOC only

Country:

JP Japan

Kind:

Inventor(s):

KUMAGAI YOUZOU

Applicant(s):

HITACHI LTD

News, Profiles, Stocks and More about this company

Issued/Filed Dates:

Sept. 8, 1984 / March 2, 1983

Application Number:

JP1983000032786

IPC Class:

B22C 1/12; B22C 9/06; B22D 17/22; C22C 9/00; C22F 1/08;

Abstract:

Purpose: To prevent deformation of a metallic mold for casting and to improve durability by using a copper alloy consisting of zirconium and titanium of limited components and a compd. of one thereof and copper for said metallic mold.

Constitution: A metallic mold is cast of a copper alloy contg. 0.01W3W% zirconium and 0.03W5W% titanium and a compd. of either one of zirconium and titanium and copper. The metallic mold having =100 Brinell hardness Hs at an ordinary temp. and =20% conductivity is then cast. The mold is subjected to a soln. heat treatment and an aging treatment in order to make the copper alloy into the texture in which the precipitation phase exists in dispersion. The reason for limiting the components of the zirconium and titanium

lies in that if the zirconium is above the limited content, the

conductivity decreases and hardness is not expected. If the titanium is above the limited content, embrittleness arises in the material and

the conductivity decreases.

COPYRIGHT: (C)1984, JPO& Japio

Other Abstract Info:

none

Foreign References:

Show the 1 patents that reference this one

Powered by DB2 and Net, Data

Alternative Searches







Nominate this invention for the Gallery...

Browse



J.S. Class by title <u>by number</u>



Privacy | Legal | Gallery | IP Pages | Advertising | FAQ | Contact Us